

eukula Products 2011

eu
ki
v
u
e

Natural products demand environmentally friendly protection.



Based in the Black Forest Frei Lacke, a high-profile and long-established company focuses its business activities on a combination of innovative technology and sustainability of product and process. eukula, a wholly-owned subsidiary of Frei Lacke, benefits from the development power, know-how and highly-automated production technologies of Frei Lacke. This synergy enables the eukula team to find practical solutions for the treatment of all types of wood floorings. Our activities are focused on the protection of floors and their maintenance. Since 1963, when eukula decided to start its business in the wood floor market, our products have proven their excellence.

eukula,
sustainable products and applications
on our customers' behalf

This is our slogan

Hans-Peter Frei

A handwritten signature in blue ink that reads "H.-P. Frei".

Dr. Rainer Frei

A handwritten signature in blue ink that reads "Dr. R. Frei".

Products

Water Based Finishes

Strato

Wood Adhesive Binder, Primer, One and Two Component Water Based Finishes

Natural and Coloured Oils

euku-oils

High Solid Oils, Hardwax Oils, Natural Oils, Coloured Oils as well as euku-exterior Oils

Conventional Systems

H

Wood Adhesive Binder

G

Primer for Roller and Trowel Application

UA

One Component Finishes

PU

Two Component Finishes

Product Supplements

Care and Maintenance Products

Tools and Accessories

Strato[®]

STRATO

Wood Adhesive Binder

Primer

One Component Water Based Finishes

Two Component Water Based Finishes



Strato 101



Wood Adhesive Binder. Water based binder for the preparation of wood filler.

Mix Strato 101 with clean sanding dust from the last sanding stage and mix to a trowelable consistency. Use only a stainless steel trowel. The floor may be sanded after approx 30-60 min.

- quick drying
- good filling power
- no darkening under oiled floors
- easy to use

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 101	500019	10l	-	50-100 ml/m ²	10-20 m ² /l	30-60 min	40	-	
Strato 101	500019	5l	-	50-100 ml/m ²	10-20 m ² /l	30-60 min	90	-	

Strato 110



Joint Adhesive Powder. A dispersion powder for the preparation of wood filler in different colours. Add approx 70% water to achieve the working consistency. Use a stainless steel trowel and apply within 45 to 60 min. Colours: oak, beech, pine/maple/ash.

- solvent-free
- low shrinkage
- readily sandable
- low odour

Giscode: W1

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 110	975000	5l	oak	50-100 ml/m ²	10-20 m ² /l	45-60 min	36	-	
Strato 110	975001	5l	beech	50-100 ml/m ²	10-20 m ² /l	45-60 min	36	-	
Strato 110	975002	5l	pine/maple/ash	50-100 ml/m ²	10-20 m ² /l	45-60 min	36	-	

Strato 200



Primer for roller application. Water based primer for all types of wood as well as cork floors. Use the universal roller for application. The surface may be sealed with any Strato water based finish after about 30 - 90 min. without intermediate sanding.

- strong barrier effect
- reduces side bonding
- good elasticity
- low in odour
- suitable for underfloor heating

Giscode: W2+

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 200	700010	10l	-	100-120 ml/m ²	8,5-10 m ² /l	30-60 min	40	-	
Strato 200	700010	5l	-	100-120 ml/m ²	8,5-10 m ² /l	30-60 min	90	-	

Strato 201



Primer for trowel application. Water based primer for application with a stainless steel trowel. Can be overcoated after a drying time of about 20 - 30 min.

- no intermediate sanding is required
- no trowel traces
- quick drying
- also suitable for highly absorbing woods

Giscode: W2+

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 201	700011	10l	-	30-50 ml/m ²	20-35 m ² /l	20-30 min	30	-	
Strato 201	700011	5l	-	30-50 ml/m ²	20-35 m ² /l	20-30 min	72	-	

Giscode: W1+ = Water based surface treatment agents, without solvents, NMP-free

W2+ = Water based surface treatment agents, solvent content up to 5 %, NMP-free

Strato 202



Gel for trowel application. Closes hairline cracks and gaps. Apply the gel, using a stainless steel trowel, to the sanded Strato finish to achieve an even, joint free surface.

- no intermediate sanding
- no trowel traces
- quick drying
- may be applied on any Strato water based finish

Giscode: W2+

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 202	700012	5l		30-50 ml/m ²	20-35 m ² /l	2-3 hrs	72	-	





Strato Domicile satin / matt



One component water based finish for normally frequented areas, e.g. living areas. Also suitable for sealing floors treated with euku-naturöl, euku-öl 1 HS or euku-coloröl.

- excellent flow
- non yellowing
- easy to use

Giscode: W3+

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato Domicile	500002	10l	satin	130 ml/m ²	ca. 8 m ² /l	approx 6 hrs	40	-	
Strato Domicile	500002	5l	satin	130 ml/m ²	ca. 8 m ² /l	approx 6 hrs	90	-	
Strato Domicile	500003	10l	matt	130 ml/m ²	ca. 8 m ² /l	approx 6 hrs	40	-	
Strato Domicile	500003	5l	matt	130 ml/m ²	ca. 8 m ² /l	approx 6 hrs	90	-	





Strato 341 satin / Strato 342 matt



One component water based finish, easy to use, for normally frequented areas, e.g. living areas.

- excellent flow
- abrasion resistant
- resistant against household chemicals

Giscode: W3+

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 341	500004	10l	satin	130 ml/m ²	ca. 8 m ² /l	approx 6 hrs	40	-	
Strato 341	500004	5l	satin	130 ml/m ²	ca. 8 m ² /l	approx 6 hrs	90	-	
Strato 342	500005	10l	matt	130 ml/m ²	ca. 8 m ² /l	approx 6 hrs	40	-	
Strato 342	500005	5l	matt	130 ml/m ²	ca. 8 m ² /l	approx 6 hrs	90	-	

Strato 310 gloss / Strato 311 satin



Versatile one component water based finish for highly frequented living areas. A highly abrasion resistant sealing of wood and cork floors for the living area is achieved if applying our recommended system.

Giscode: W3+

- good flow
- good abrasion resistance
- accentuates the natural beauty of the wood

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 310	500000	10l	gloss	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Strato 310	500000	5l	gloss	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	90	-	
Strato 311	500001	10l	satin	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Strato 311	500001	5l	satin	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	90	-	



Strato 370 gloss / Strato 371 satin / Strato 372 matt



Quick drying **one component water based finish**, especially suitable for light woods. For wood and cork floors in highly frequented areas, e.g. living areas.

Giscode: W2+

- good abrasion resistance
- resistant against household chemicals
- non yellowing
- Strato 371 resists scuffs and marks

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 370	500008	10l	gloss	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Strato 370	500008	5l	gloss	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	90	-	
Strato 371	500009	10l	satin	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Strato 371	500009	5l	satin	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	90	-	
Strato 372	500010	10l	matt	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Strato 372	500010	5l	matt	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	90	-	

Strato Quick Start / Strato Quick Finish satin



One Day Coating System

Water Based **One Day Coating System** for living areas. Trowel three times with Strato Quick Start and apply the Strato Quick Finish once with a roller - the floor will be ready within one day. Big savings due to less working hours and travelling.

Giscode: Quick Start= W2+, Quick Finish= W3+

- no intermediate sanding
- easy to use
- very high abrasion resistance

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato Quick Start	700014	10l	-	30 ml/m ²	approx 35 m ² /l	approx 20 min	42	-	
Strato Quick Start	700014	5l	-	30 ml/m ²	approx 35 m ² /l	approx 20 min	72	-	
Strato Quick Finish	500011	10l	satin	190 ml/m ²	approx 5 m ² /l	approx 12 hrs	40	-	
Strato Quick Finish	500011	5l	satin	190 ml/m ²	approx 5 m ² /l	approx 12 hrs	90	-	

Giscode: W2+ = Water based surface treatment agents, solvent content up to 5 %, NMP-free
W3+ = Water based surface treatment agents, solvent content up to 15%, NMP-free





Strato 331 satin / Strato 332 matt

Staircase Finish

One component water based finish for staircases, application by roller or spraying.

- good abrasion resistance
- non yellowing
- quick drying and readily sandable

Giscode: W2+

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 331	500015	10l	satin	130 ml/m ²	approx 8 m ² /l	4-6 hrs	40	-	
Strato 331	500015	10l	satin	70 ml/m ²	approx 15 m ² /l	30-40 min	40	-	
Strato 332	500016	10l	matt	130 ml/m ²	approx 8 m ² /l	4-6 hrs	40	-	
Strato 332	500016	10l	matt	70 ml/m ²	approx 15 m ² /l	30-40 min	40	-	







Strato 461 satin / Strato 462 matt / Strato 463 ultra matt

Two component water based finish for extremely frequented areas. Mixing ratio: 10:1 with Strato 460 Hardener.

Also for oil / water based combination using the oil (euku-naturöl, euku-öl 1 HS or euku-coloröl) as primer. Spraying is also possible after dilution with water.

- non yellowing
- extremely high abrasion resistance
- Strato 461 anti-slip for sport floors
- Strato 461 not susceptible to shoemarks

Giscode: W3+

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato 461	500029	9l	satin	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Duo Pack Strato 461	500500	2x4,5l+2x0,45l	satin	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	30	-	
Strato 462	500031	9l	matt	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Duo Pack Strato 462	500600	2x4,5l+2x0,45l	matt	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	30	-	
Strato 463	500033	9l	ultra matt	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Duo Pack Strato 463	500700	2x4,5l+2x0,45l	ultra matt	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	30	-	
Strato 460 Hardener	500030	0,9l	Hardener					8	



There is a video clip available on our home-page, www.eukula.de:
Finish with 2C Water Based Sealer


Strato pro satin

Water based **two component polyurethane finish** with increased slip-resistance for extremely frequented areas, e.g. canteens, restaurants etc., also suitable for light wood and cork floors. Mixing ratio: 10:1 with Strato 460 Hardener.

(according to rule BGR 181 of the German Employers' Liability Insurance Association).

- extreme high abrasion resistance
- non yellowing
- increased slip-resistance (R9) according to rule BGR 181 of the Germany Employers' Liability Insurance Association).
- not susceptible to shoemarks

Giscode: W3+

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
Strato PRO	500032	9l	satin	130 ml/m ²	approx 8 m ² /l	approx 6 hrs	40	-	
Strato 460 Hardener	500030	0,9l	Hardener				-	8	

Giscode: W2+ = Water based surface treatment agents, solvent content up to 5 %, NMP-free
W3+ = Water based surface treatment agents, solvent content up to 15%, NMP-free

Strato One Component Line Paints



Line paints for marking playing fields in sport halls.
For roller application on sanded (120 grit) Strato two component sealed sports floors.
The marking is applied after the first coat.

- Line paints for Strato sealed sports floors

Giscode: W2+

Product	Item No	Contents	Colour	Carton	Tool
Strato Line Paint	972001	1l	white / RAL 9010	8	
Strato Line Paint	972002	1l	black / RAL 9005	8	
Strato Line Paint	972003	1l	orange / RAL 2003	8	
Strato Line Paint	972004	1l	blue / RAL 5010	8	
Strato Line Paint	972005	1l	green / RAL 6010	8	
Strato Line Paint	972006	1l	yellow / RAL 1021	8	
Strato Line Paint	972007	1l	red / RAL 3000	8	

Strato UV Filter

Additive for all water based Strato finishes to protect wood from discoloration.

- prevents from discoloration
- suitable for all Strato finishes

Giscode: W2+

Product	Item No	Contents
Strato UV Filter	500017	0,5 l

SYSTEM: Traditional Coating Pure Coating One Day Coating Oil / Finish Coating

	Strato 101 Wood Adhesive Binder with Sanding Dust ⌚ approx 30 min →	Strato 101 Wood Adhesive Binder with Sanding Dust ⌚ approx 30 min →	Strato 101 Wood Adhesive Binder with Sanding Dust ⌚ approx 30 min →	Strato 101 Wood Adhesive Binder with Sanding Dust ⌚ approx 30 min →
	Strato 200 Roller primer reduces side bonding ⌚ approx 30 min →	Strato 1 Comp. or 2 Comp. Finish ⌚ approx 6 hrs →	2x Strato Quick Start Trowel Primer ⌚ 20 min each →	euku-öl 1 HS to be padded within 15 min. ⌚ approx 12-24 hrs →
	Strato 1 Comp. or 2 Comp. Finish ⌚ approx 6 hrs →	Strato 1 Comp. or 2 Comp. Finish ⌚ approx 6 hrs →	1x Strato Quick Start Trowel Primer ⌚ approx 1 hrs →	Strato 2 Comp. Finish or Strato Domicile ⌚ approx 6 hrs →
	Strato 1 Comp. or 2 Comp. Finish ⌚ approx 6 hrs →	Strato 1 Comp. or 2 Comp. Finish ⌚ approx 6 hrs →	Strato Quick Finish Strato 1 Comp. Finish ⌚ approx 12 hrs →	Strato 1 Comp. or 2 Comp. Finish ⌚ approx 6 hrs →
	⌚ Final Hardness after approx 7 days	⌚ Final Hardness after approx 7 days	⌚ Final Hardness after approx 7 days	⌚ Final Hardness after approx 7 days

Giscode: W2+ = Water based surface treatment agents, solvent content up to 5 %, NMP free

euku-öle

euku-öle

High Solid Oils

Hardwax Oils

Natural Oils

Coloured Oils

Oils for Exterior Application

Maintenance Products



euku-öl

euku-öl 1 HS



This **High Solid Oil** is based on natural oils and alkyd-resins. The oil gives the wood floor a natural matt sheen with a high abrasion resistance. The euku-öl 1 HS has a solid content of approx. 90%. The oil is applied with a trowel, padded with a beige pad and polished immediately afterwards.

- easy to use
- suitable for underfloor heating
- anti-slip R9 according to BGR 181 (German Employers' Liability Insurance Association).
- primer for Strato Domicile and for Strato 2 Component Finishes

Giscode: Ö 40

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-öl 1 HS	220000	10l	30 ml/m ²	approx 30 m ² /l	12 hrs	50	-	
euku-öl 1 HS	220000	5l	30 ml/m ²	approx 30 m ² /l	12 hrs	84	-	
euku-öl 1 HS	220000	1l	30 ml/m ²	approx 30 m ² /l	12 hrs	480	8	

euku-öl 2 Plus HS



Hardwax Oil based on natural oils and waxes with a solid content of about 80%. The oil is applied with a trowel, padded with a beige pad and polished immediately afterwards.

- oiling and waxing in one step
- suitable for underfloor heating
- gives the wood floor a natural satin sheen
- anti-slip R9 according to BGR 181 (German Employers' Liability Insurance Association).

Giscode: Ö 60

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-öl 2 Plus HS	220002	10l	30 ml/m ²	approx 30 m ² /l	12 hrs	50	-	
euku-öl 2 Plus HS	220002	5l	30 ml/m ²	approx 30 m ² /l	12 hrs.	84	-	
euku-öl 2 Plus HS	220002	1l	30 ml/m ²	approx 30 m ² /l	12 hrs	480	8	

euku-öl 3 Plus white



White tinted hardwax oil based on natural oils and waxes. Solid content about 70% which gives the floor a natural satin sheen. The oil is applied with a trowel and treated with a beige pad and polished immediately afterwards.

- Tinting, oiling and waxing in one step
- maintains the grain of the wood
- white accentuated satin finish

Giscode: Ö 60

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-öl 3 Plus weiß	220004	5l	30 - 50 ml/m ²	approx 30 m ² /l	12 hrs	84	-	
euku-öl 3 Plus weiß	220004	1l	30 - 50 ml/m ²	approx 30 m ² /l	12 hrs	480	8	

euku-naturöl



An ecological **oil impregnation based on pure vegetable oils** for an open-pore and natural wood surface. It has a solid content of approx. 97% and can be used for all wood floors to get a natural matt sheen. The oil is applied with a trowel and padded and polished immediately afterwards.

- accentuates the grain of the wood
- low consumption
- 97% solid content

Giscode: Ö 20

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-naturöl	220008	5l	30 ml/m ²	approx 30 m ² /l	12 hrs	84	-	
euku-naturöl	220008	1l	30 ml/m ²	approx 30 m ² /l	12 hrs	480	8	

Giscode: Ö 20 = Oils/Waxes, low in solvents, aromatics removed
 Ö 40 = Oils/waxes, solvent content up to 15%, aromatics removed
 Ö 60 = Oils/waxes, high in solvents (>=15%), aromatics removed

euku-coloröl



One component coloured oil based on renewable primary products. euku-coloröl is a factory-coloured system with intensive colour effects giving an even and beautiful colouration. Ask for the colour map or have a look at www.eukula.de

- even colouring without overlapping
- solvent content less 5%
- primer for Strato Domicile and Strato 2C Finishes
- cobalt-free
- mixable among each other

Giscode: Ö 20

Product	Item No	Contents	Colour	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-coloröl	220100	1l	Tabak	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220100	5l	Tabak	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220101	1l	Schnee	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220101	5l	Schnee	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220102	1l	Mokka	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220102	5l	Mokka	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220103	1l	Koralle	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220103	5l	Koralle	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220104	1l	Honig	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220104	5l	Honig	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220105	1l	Farn	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220105	5l	Farn	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220106	1l	Azur	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220106	5l	Azur	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220107	1l	Zimt	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220107	5l	Zimt	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220108	1l	Bernstein	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220108	5l	Bernstein	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220109	1l	Silber	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220109	5l	Silber	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220110	1l	Rubin	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220110	5l	Rubin	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	
euku-coloröl	220111	1l	Terra	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	480	8	
euku-coloröl	220111	5l	Terra	30 ml/m ²	approx 30 m ² /l	max. 12 hrs	84	-	

Giscode: Ö 20 = Oils/waxes, low in solvents, aromatics removed

euku-öl for exterior application

euku-exterior Öl PRO



Special oil for exterior application for all types of wood based on vegetable oils. The PRO quality is primarily used for application on untreated resp. heavily weathered wood. The exterior oil will guarantee the lasting beauty of your floor. All our quality oils are based on renewable raw materials. The exterior oil PRO is applied with a brush or cloth.

- UV protection
- high solid content
- quick drying

Giscode: Ö 60

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-exterior Oil PRO	221000	10l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	50	-	
euku-exterior Oil PRO	221000	5l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	84	-	
euku-exterior Oil PRO	221000	1l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	480	8	

euku-exterior Öl BASIC



Oil for exterior application to refresh all types of wood. The euku-exterior Öl BASIC is used to refresh the already treated floor resp. is suitable for the ongoing maintenance. The oil is based on vegetable oils and has a gentle smell. The exterior oil will guarantee the lasting beauty of your floor. All our quality oils are based on renewable raw materials. The exterior oil BASIC is applied with a brush or cloth.

- UV protection
- quick drying

Giscode: Ö 60

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-exterior Oil BASIC	221002	10l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	50	-	
euku-exterior Oil BASIC	221002	5l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	84	-	
euku-exterior Oil BASIC	221002	1l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	480	8	

euku-exterior Öl teak PRO



Teak tinted oil for exterior application for all types of wood based on vegetable oils. The euku-exterior oil teak quality is primarily used for application on untreated resp. heavily weathered wood. The exterior oil will guarantee the lasting beauty of your floor. All our quality oils are based on renewable raw materials. The oil is applied with a brush or cloth.

- UV protection
- high solid content
- quick drying

Giscode: Ö 60

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-exterior Oil PRO	221001	10l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	-	50	
euku-exterior Oil PRO	221001	5l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	-	84	
euku-exterior Oil PRO	221001	1l	80 ml/m ²	approx 12 m ² /l	approx 12 hrs	480	8	

euku-conditioner



The **euku-conditioner revives and cleans the wood surface** which has been subject to greying (e.g. decking, terraces, facades, furniture)

- biologically degradable
- easy to apply
- cleans the surface

Giscode: GG40

Product	Item No	Contents	Consumption	Coverage	Pal.	Carton	Tool
euku-conditioner	950008	5l	50-80 ml/m ²	approx 15 m ² /l	84	-	
euku-conditioner	950008	1l	50-80 ml/m ²	approx 15 m ² /l	408	8	

Giscode: Ö 40 = Oils/waxes, solvent content up to 15%, aromatics removed
 Ö 60 = Oils/waxes, high in solvents (>=15%), aromatics removed
 GG 40 = Stripper, irritant, solvent free

euku-refresher







Refreshing of Oiled Floors

The ideal maintenance for floors treated with hardwax oil. Apply the euku-refresher thinly and evenly with a trowel, T-Frame or cloth and let it penetrate. Pad the wet film and polish it afterwards.

Giscode: Ö 60

- for maintaining the natural surface
- optimises the durability
- can be repaired spot-wise

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-refresher	220003	5l	30 ml/m ²	approx 30 m ² /l	approx 1 hr	84	-	 
euku-refresher	220003	1l	30 ml/m ²	approx 30 m ² /l	approx 1 hr	480	8	 

euku-pflegeöl







Maintenance for oiled floors

Recommended for floors treated with euku-öl 1 HS. Should be applied according to wear and tear, e.g. once or twice for the domestic area and more often for strongly frequented areas.

Pad the wet film and polish it afterwards.

Giscode: Ö 60

- good penetration properties
- low in odour
- rejuvenates wooden floors


























Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-pflegeöl	220001	3l	30 ml/m ²	approx 30 m ² /l	approx 1 hr	30	6	 
euku-pflegeöl	220001	1l	30 ml/m ²	approx 30 m ² /l	approx 1 hr	480	8	 

SYSTEM:

Oil System

Hardwax Oil System

Oil / Finish System

1	 H 99 or H 99 S Wood adhesive binder with sanding dust approx 20 min → 	 Strato 101 Wood adhesive binder with sanding dust approx 30 min → 	 Strato 101 Wood adhesive binder with sanding dust approx 30 min → 
2	 euku-öl 1 HS Impregnation for matt surfaces - to be padded within 15 min approx 15 min → 	 euku-öl 2 Plus HS Oiling and waxing in one step - to be padded within 15 min approx 15 min → 	 euku-öl 1 HS, euku-naturöl or euku-coloröl Impregnation to be padded within 15 min, approx 12 hrs 
3	 euku-pflegeöl to be padded within 15 min. approx 1 hr → 	 euku-refresher to be padded within 15 min approx 1 hr → 	 Strato 2 C Finish or Strato Domicile approx 6 hrs → 
4	 afterwards polish with a polishing cloth euku-öl 1 HS + euku-pflegeöl = matt	 afterwards polish with a polishing cloth euku-öl 2 Plus HS + euku-refresher = satin	 Strato 2 C finish or Strato Domicile approx 6 hrs → 
	 fully stressable after 8 days	 fully stressable after 8 days	 Final hardness after approx 7 days



See our video clip
Oiling in One Day
under www.eukula.de

euKu-classics

H

Wood Adhesive Binder

G

Primer

UA

One Component Finishes

PU

Two Component Finishes



H Wood Adhesive Binder, G Primer

H 99 / H 99 S



Solvent Based **Wood Adhesive Binder**

Mix wood adhesive binder with the sanding dust. H 99/H99s is used to level or fill joints, indentations or cracks. Use a stainless steel trowel only.

- quick drying
- easily sandable
- for all parquet finishes and oils
- H 99 S is lower in odour and quicker sandable

Giscode: G3

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
H 99	900005	10l	100 ml/m ²	approx 10 m ² /l	20-30 min	50	-	
H 99	900005	5l	100 ml/m ²	approx 10 m ² /l	20-30 min	84	-	
H 99 S	900006	10l	100 ml/m ²	approx 10 m ² /l	20-30 min	30	-	
H 99 S	900006	5l	100 ml/m ²	approx 10 m ² /l	20-30 min	72	-	

G 200



Solvent Based **Primer for roller application.**

Apply PU or UA finish without intermediate sanding.

- quick drying
- for exotic woods
- preserves the natural color of the wood
- no intermediate sanding

Giscode: G3

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
G 200	700000	10l	100 ml/m ²	approx 10 m ² /l	30-40 min	30	-	
G 200	700000	5l	100 ml/m ²	approx 10 m ² /l	30-40 min	84	-	

G 240



Solvent based **trowel primer for the UA non stop trowel application.**

Trowel twice criss-cross with a stainless steel trowel. Then apply a UA finish without intermediate sanding.

- quick drying
- good barrier effect
- good filling power

Giscode: G2

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
G 240	700004	10l	30-40 ml/m ²	approx 25-30 m ² /l	approx 30 min	30	-	

Giscode: G2 = Base sealants and plastic woods, aromatics removed containing low-boiling compounds
 G3 = Base sealants and plastic woods, containing aromatics and low-boiling compounds

UA 490 gloss / UA 491 satin



Solvent based **one component finish** for sports floors. Highly resistant to mechanical abrasion and quick drying. The finish is applied with a roller. Adjust viscosity for spraying by adding V 28 Dilution.

- anti-slip for sports floors
- suitable for underfloor heating
- minimized side bonding

Giscode: KH1

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
UA 490	200001	10l	gloss	100-120 ml/m ²	approx 10 m ² /l	approx 24 hrs	30	-	
UA 491	200002	10l	satin	100-120 ml/m ²	approx 10 m ² /l	approx 24 hrs	30	-	

UA 510 gloss / UA 511 satin / UA 512 matt



Solvent based **one component finish** to be applied with a roller. Suitable for normally frequented areas, e.g. living areas.

- reduces side bonding
- high mechanical and good chemical resistance
- free of lead and aromatics

Giscode: KH1

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
UA 510	200005	10l	gloss	100-120 ml/m ²	approx 10 m ² /l	approx. 12 hrs	30	-	
UA 511	200006	10l	satin	100-120 ml/m ²	approx 10 m ² /l	approx 12 hrs	30	-	
UA 512	200008	10l	matt	100-120 ml/m ²	approx 10 m ² /l	approx 12 hrs	30	-	

UA 210 Trowel Gel

Solvent based **gel for trowel application**. Closes hairline cracks and gaps.

Apply the gel, using a stainless steel trowel to the sanded UA sealer to achieve an even, joint free surface. Then finish the floor with a UA finish.

- free of formaldehyd
- good filling power

Giscode: KH1

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Tool
UA 210	200009	5l	-	30-50 ml/m ²	approx 20-35m ² /l	6-8 hrs	

UA One Component Line Paint



Solvent based **paint for marking lines (sport halls)**.

For roller application on a sanded (120 grit) UA sealed sports floors. The line paint is applied after the first coat.

- Line Paint
- for UA sealed sports floors

Giscode: KH1

Product	Item No	Contents	Colour	Carton	Tool
UA One Component Line Paint	970001	1l	white / RAL 9010	8	
UA One Component Line Paint	970002	1l	black / RAL 9005	8	
UA One Component Line Paint	970003	1l	red / RAL 3000	8	
UA One Component Line Paint	970004	1l	blue / RAL 5010	8	
UA One Component Line Paint	970005	1l	green / RAL 6010	8	
UA One Component Line Paint	970007	1l	yellow / FR 811	8	
UA One Component Line Paint	970008	1l	orange / RAL 2003	8	

Giscode: KH1 = Oil epoxy resin sealant, high in solvents, aromatics removed (solvent content >15%)

V 28



UA Dilution

Product	Item No	Contents	Palett	Carton
V 28	800003	10l	50	-
V 28	800003	5l	84	-
V 28	800003	1l	480	8

PU 450 high gloss + PU 450 Hardener



Solvent based **two component finish**. Mixing ratio: 1:1 with PU 450 Hardener. To be applied with a roller. In case of spraying the material should be diluted by adding V 25.

- highest resistance against chemical and mechanical wear
- for extremely high frequented areas
- airless spraying possible

Giscode: DD2

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
PU 450	100003	10l	high gloss	100-150 ml/m ²	approx 6 m ² /l	12-16 hrs	30		
PU 450	100003	5l	high gloss	100-150 ml/m ²	approx 6 m ² /l	12-16 hrs	84		
PU 450 Härter	100007	10l	-						
PU 450 Härter	100007	5l	-						

PU 550 gloss / PU 551 satin + PU 550 Hardener



Solvent based **two component finish**. Mixing ratio: 1:1 with PU 550 Hardener. To be applied with a roller. Use PU 450 as a primer for highly frequented areas and exotic woods.

- 100% PU sealing
- extremely high resistance against chemical and mechanical wear

Giscode: DD2

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
PU 550	100005	10l	gloss	120-150 ml/m ²	approx 7 m ² /l	12-16 hrs	30	-	
PU 550	100005	5l	gloss	120-150 ml/m ²	approx 7 m ² /l	12-16 hrs	84	-	
PU 551	100006	10l	satin	120-150 ml/m ²	approx 7 m ² /l	12-16 hrs	30	-	
PU 551	100006	5l	satin	120-150 ml/m ²	approx 7 m ² /l	12-16 hrs	84	-	
PU 550 Härter	100008	10l	-						
PU 550 Härter	100008	5l	-						

V 25



PU Thinner

Product	Item No	Contents	Pal.	Carton
V 25	800000	10l	50	-
V 25	800000	5l	84	-
V 25	800000	1l	480	8

Giscode: DD2 = Polyurethane sealants, high in solvents, containing aromatics (solvent content >15%)

UA One Component Finishes, PU Two Component Finishes

SYSTEM:

Finish with Primer

Pure Finish System

Sports Floor

1	H 99 S Wood Adhesive Binder with sanding dust approx 20 min →	H 99 S Wood Adhesive Binder with sanding dust approx 20 min →	UA 491 One Comp. Finish to be diluted with V28 approx 8 hrs →
2	G 200 Universal Wood Primer with reduced side bonding approx 30 min →	UA 510 / 511 / 512 One Comp. Finish + 10-20% V28 UA Dilution approx 6 hrs →	UA One Component Line Paint approx 12 hrs →
3	UA 491 One Comp. Finish approx 16 hrs →	UA 510 / 511 / 512 One Comp. Finish approx 12 hrs →	UA 491 One Comp. Finish approx 16 hrs →
4	UA 491 One Comp. Finish approx 24 hrs →	UA 510 / 511 / 512 One Comp. Finish approx 24 hrs →	UA 491 One Comp. Finish approx 24 hrs →
	Final hardness after 8 days	Final hardness after 8 days	Final hardness after 8 -10 days

NON-STOP-

Trowel Application: UA

Trowel Application: PU

1	H 99 S Wood Adhesive Binder with sanding dust approx 20 min →	H 99 S Wood Adhesive Binder with sanding dust approx 20 min →
2	G 240 or G 280 Trowel Primer approx 10 min →	G 280 Trowel Primer approx 10 min →
3	G 240 or G 280 Trowel Primer approx 40 min →	G 280 Trowel Primer approx 40 min →
4	UA 510 / 511 / 512 One Comp. Finish approx 24 hrs →	PU 551 + PU 550 Härter Two Comp. Finish approx 12 hrs →
	Final hardness after 8 days	Final hardness after 8 days

eukula

Care and Maintenance Products

Tools and Accessories






euku-wax



To protect sealed wood, cork, synthetic and stone floors as well as sports floors.
Anti-slip according to 18032. Apply euku-wax thinly and evenly on the clean and dry floor by using an eukula floor mop or soft cloth.

- also for sports floors
- self-shining
- wipe-proof
- for all sealed floors

Giscode: GE10

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-wax	950002	10l	gloss	35 ml/m ²	approx 30 m ² /l	approx 30 min	60	-	
euku-wax	950002	3l	gloss	35 ml/m ²	approx 30 m ² /l	approx 30 min	144	6	
euku-wax	950002	1l	gloss	35 ml/m ²	approx 30 m ² /l	approx 30 min	360	15	


euku-mattwax



To protect sealed wood, cork, synthetic and stone floors.
Apply euku-mattwax thinly and evenly on the clean and dry (matt sealed) floor by using an eukula floor mop or soft cloth.

- the perfect protection for matt sealed floors
- ready to use

Giscode: GE10

Product	Item No	Contents	Degree of Gloss	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-mattwax	950013	1l	matt	35 ml/m ²	approx 30 m ² /l	approx 30 min	360	15	



euku-wachsentferner



Wax remover with active solvent.
Special solvent for removing shiny or bees wax coatings on heavily soiled floors.

- mixable with water
- low-foam special cleaner
- heavily diluted, also suitable for use as a general cleaner (on-going cleaning)

Giscode: GG20

Product	Item No	Contents	Consumption	Pal.	Carton	Tool
euku-wachsentferner	950006	5l	1-2.5l / 10l water	90	-	
euku-wachsentferner	950006	1l	1-2.5l / 10l water	480	12	



euku-clean



euku-clean to be diluted with water for cleaning sealed wood, cork and other water resistant floors.

- effectice cleaning concentrate
- for cleaning sealed floors

Giscode: GU70

Product	Item No	Contents	Consumption	Drying Time	Pal.	Carton	Tool
euku-clean	950012	10l	50-100 ml/10l water	approx 30 min	60	-	
euku-clean	950012	1l	50-100 ml/10l water	approx 30 min	480	6	

Giscode: GE10 = Emulsions/Dispersions (containing tensides)

GG20 = Stripper, containing solvents without skinresorptive substances, not labeled

GU70 = Maintainer, irritant, without solvents

euku-clean Spray

Ready-to-use **cleaning spray** for all sealed wood and cork floors. Just spray and wipe with a dry cloth.

- wipe and spray
- for fast cleaning in between

Giscode: GU40

Product	Item No	Contents	Pal.	Carton
euku-clean Spray	950014	1l	480	12

euku-polish Plus

Solvent based **floor care**

Spread euku-polish plus thin on the cleaned floor by using a cloth or mop and polish the floor as soon as it is dry.

- for all sealed and impregnated floors
- for solvent resistant floors
- water proof
- easy to polish

Giscode: GU55

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton
euku-polish Plus	950010	10l	10-20 ml/m ²	approx 50-100 m ² /l	approx 30 min	50	-
euku-polish Plus	950010	1l	10-20 ml/m ²	approx 50-100 m ² /l	approx 30 min	336	12

euku-reiniger

Solvent based **strong cleaner for impregnated wood floors.**

Cleaner for the basic and intermediate cleaning of wood, stone and synthetic floors maintained with wax.

- strong cleaner for waxy, greasy and dirty floor surfaces
- removes stains and shoemarks
- deep cleaner for floors treated with euku-pflegeöl, euku-polish Plus and euku-refresher

Giscode: GG50

Product	Item No	Contents	Pal.	Carton
euku-reiniger	950011	10l	50	-
euku-reiniger	950011	1l	360	12



euku-pflege-emulsion

Maintenance emulsion for oiled wood floors.

To be mixed with water for wiping up with a lightly damp cloth.

- for cleaning and maintenance
- the perfect maintenance care
- conserves the natural surface

Giscode: GU40

Product	Item No	Contents	Consumption	Drying Time	Pal.	Carton	Tool
euku-pflege-emulsion	950009	5l	0,1-0,2l/10l water	approx 1 hr	90	-	
euku-pflege-emulsion	950009	1l	0,1-0,2l/10l water	approx 1 hr	480	8	

Giscode: GU40 = Maintainer, without solvents, containing surfactants

GU55 = Maintainer, flammable, containing solvents without skinresorptive substances

euku-refresher







Refreshing of Oiled Floors

The ideal maintenance for floors treated with hardwax oil. Apply the euku-refresher thinly and evenly with a trowel, T-Frame or cloth and let it penetrate. Pad the wet film and polish it afterwards.

Giscode: Ö 60

- for maintaining the natural surface
- optimises the durability
- can be repaired spot-wise

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-refresher	220003	5l	30 ml/m ²	approx 30 m ² /l	approx 1 hr	84	-	 
euku-refresher	220003	1l	30 ml/m ²	approx 30 m ² /l	approx 1 hr	480	8	 

euku-pflegeöl







Maintenance for oiled floors

Recommended for floors treated with euku-öl 1 HS. Should be applied according to wear and tear, e.g. once or twice for the domestic area and more often for strongly frequented areas.

Pad the wet film and polish it afterwards.

Giscode: Ö 60

- good penetration properties
- low in odour
- rejuvenates wooden floors

Product	Item No	Contents	Consumption	Coverage	Drying Time	Pal.	Carton	Tool
euku-pflegeöl	220001	3l	30 ml/m ²	approx 30 m ² /l	approx 1 hr	30	6	 
euku-pflegeöl	220001	1l	30 ml/m ²	approx 30 m ² /l	approx 1 hr	480	8	 

euku-pflegeset 1 + 2





Maintenance set for sealed floors

A practical take away set with a maintenance and care product for the sealed floor. The perfect care for your wood floor.

- perfectly adjusted
- practical take-away box

Giscode: Set 1=GE10 + GU70,
Set 2=GU55 + GU50

Product	Item No	Contents	Palett	Carton	Tool
euku-pflegeset 1	950004	1l euku-wax + 1l euku-clean	-	7	
euku-pflegeset 2	950005	1l euku-polish Plus + 1l euku-reiniger	-	7	



There are video clips available on our homepage, www.eukula.com:

Cleaning and Maintenance of Sealed wood Floors and Maintenance of Oiled Wood Floors

Giscode: Ö 60 = Oils/waxes, high in solvents (>=15%), aromatics removed
 GE10 = Dispersions/ Coating products (contains surfactants)
 GU50 = Maintainer, containing solvents without skinresorptive substances
 GU55 = Maintainer, flammable, containing solvents without skinresorptive substances
 GU70 = Maintainer, irritant, without solvents

V 29

Washing Dilution

Product	Item No	Contents	Palett	Carton
V 29	800004	10l	50	-
V 29	800004	5l	84	-
V 29	800004	1l	480	8

euku-plast

Polyacrylic based **joint sealer**

- silicon-free
- sandable and long lasting elasticity
- over-coatable

Product	Item No	Contents	Colour	Drying Time	Palett	Carton
euku-plast	976000	0,310 l	dark oak	approx 30 min	-	12
euku-plast	976001	0,310 l	steamed beech	approx 30 min	-	12
euku-plast	976002	0,310 l	maple/ash/pine/light oak	approx 30 min	-	12
euku-plast	976003	0,310 l	walnut	approx 30 min	-	12
euku-plast	976004	0,310 l	merbau	approx 30 min	-	12
euku-plast	976005	0,310 l	light oak	approx 30 min	-	12

Care and Maintenance System

To maintain the value of a wooden floor, it is necessary to take care of a healthy living climate. This is reached at ca. 20°C and 50% relative humidity. Higher levels of relative humidity will cause the wood to swell, lower levels will cause the wood to shrink, opening up joints of varying sizes.

Simple devices such as hygrometers or thermometers enable these conditions to be monitored. By placing water containers on radiators or by using humidifiers in large rooms, it is possible to increase the humidity in a room.

Please follow our Maintenance Instructions.

Floors	Sealed Floors			
		Sports Floors		
		Hardwax Oiled Floors		Oiled Floors
euku-wax	▲ ●	▲ ●		
euku-mattwax	▲ ●			
euku-refresher			●	
euku-pflege-emulsion			■	■
euku-pflegeöl				●
euku-clean	■	■		
euku-clean spray	■	■		

▲ for First Maintenance ● for Maintenance Care ■ for Maintenance Cleaning

Sanding Grid



Sanding Grid

Diameter approx 406 mm

Product	Item No	Contents	Carton
Sanding Grid Ø 406 mm	991000	Grit 60	10
Sanding Grid Ø 406 mm	991001	Grit 80	10
Sanding Grid Ø 406 mm	991002	Grit 100	10
Sanding Grid Ø 406 mm	991003	Grit 120	10
Sanding Grid Ø 406 mm	991004	Grit 150	10
Sanding Grid Ø 406 mm	991005	Grit 180	10

Super Pad



for LL 400

Diameter approx 406 mm

Product	Item No	Contents	Carton
Super Pad Ø 406 mm	990200	white (maintain, polish)	10
Super Pad Ø 406 mm	990300	beige (oil, clean, maintain)	10
Super Pad Ø 406 mm	990500	green (clean)	10
Super Pad Ø 406 mm	990400	black (matt)	10

Multi-Purpose Machine LL 400



Electric **Single Disc Machine**

240 W, 230 V, 50 Hz, 150 rpm. working width 260 - 400 mm (for standard pads)

The convenient care and maintenance machine

Product	Item No	Contents
LL 400	990004	Multi Purpose Machine
Drive Board	990005	as replacement for LL 400

Stainless Steel Trowel



Product	Item No	Contents	Palett	Carton
Stainless Steel Trowel	980000	27 cm, for wood adhesive binder, trowel primer and oil	-	10

Strato Microstar Roller



Product	Item No	Contents	Palett	Carton
Strato Microstar Roller	980024	8 mm pile length, for water based finishes (without roller holder)	-	-

Universal Roller



Product	Item No	Contents	Palett	Carton
Universal Roller	980020	for Strato, UA and PU Finishes (without roller holder)	-	-

Roller Holder / Telescopic Rod



Product	Item No	Contents	Palett	Carton
Roller Holder	980031	for Universal and Strato Microstar Roller	-	-
Telescopic Rod	980049	for roller holder, adjustable up to 3 m	-	-

Rollerbox



Product	Item No	Contents	Palett	Carton
Rollerbox	980039	for storing cleaned rollers	-	-

Product Supplements: Tools

Cleaning Mop



Product	Item No	Contents	Palett	Carton
Cleaning Mop	980045	Applicator with cover to apply maintenance products	-	-
Replacement Cover	980046	for cleaning mop		

Dust Binding Cloth



Product	Item No	Contents	Palett	Carton
Dust Binding Cloth	980023	for dust removal	-	100

Coating Pail



Product	Item No	Contents	Palett	Carton
Coating Pail	979300	12 l, rectangular, blue, with scale	-	-
PE Bag	980015	PE bags for coating pail	-	400

T-Frame



Product	Item No	Contents	Palett	Carton
T-Frame	980053	Applicator for euku-refresher and euku-pflegeöl	-	-
Cover	980054	for T-Frame	10	-
Telescopic Rod	980056	for T-Frame, adjustable from 1,30 m up to 1,80 m	-	-

Polishing Cloth



Product	Item No	Contents	Palett	Carton
Polishing Cloth	980055	to polish and remove the surplus of euku-refresher and euku-pflegeöl for the oiling in one day system.	-	approx 250

exterior-oil brush

Product	Item No	Contents	Palett	Carton
exterior-oil brush	980050	Brush for the euku-exterior oil, 20 cm	-	-

GENERAL INFORMATION

The values indicated regarding consumption, coverage and drying times are approximate. Depending on the substrate, air temperature, humidity and way of application the values may differ and may thus only be taken as an information.


If it wasn't for you

Everything undergoes permanent change. Technology, products and personal taste are no exception. Modern technology allows for the further development of existing products and the development of new ones. Our specialists from the development and application technology are permanently looking for rational and effective fields of operation for the eukula systems. We need your active support. eukula can only react quickly to new trends if it has close connections to the market and its wide range of products and thus provide solutions to our customers' requirements.



Just let us know what you need! eukula sees itself as a partner to the flooring trade supporting them now and in future with highly-sophisticated products and modern technology and application techniques.





There are video clips available on our homepage, www.eukula.com, for each of the topics below:

- **Finish with 2C Water Based Sealer**
- **Cleaning and Maintenance of Sealed Floors**
- **Oiling in One Day**
- **Maintenance of Oiled Floors**



eukula: From Factory to Floor

As a wholly-owned subsidiary of Emil Frei GmbH & Co. KG Lackfabrik in Döggingen, Germany, eukula has all the know-how of this powerful company at its disposal.

Frei Lacke always fulfills the latest quality assurance, environmental protection and occupational health and safety requirements and continues to develop these independently with an eye to the future. Certifications such as DIN EN ISO 9001, ISO/TS 16949 and the EMAS II active environmental policy are regarded as important investments in the future.

Decades of experience in development and manufacturing provide a sound basis for laboratory work at eukula. The skills of raw material selection, procurement and quality control play a vital role.



Our team in the eukula laboratory is continually working on new and more highly developed products, for even a good product can be improved. We are able to provide unique solutions as the industry evolves while maintaining the highest quality according to our customers demand. We can find practical solutions for the treatment of the most diverse woods or the most unusual application.

Our advisory for training service informs and teaches our trade customers about products and processing techniques in their own workshops. The much sought-after eukula seminars are integrated into the training and advancement programs in flooring trade and trade businesses. These provide a forum for an exchange of ideas which point us new directions. In this way, the wealth of experience in flooring trade businesses is channelled into the development of new products.

eukula sees itself as a partner to the flooring trade.



Our Mission: To Protect Fine Wood from the Rigours of Everyday Life

Everywhere that there are wood and parquet floors eukula products can be found. We lend new splendour to expensively restored wood inlays. For instance, we brought a silk matt elegance to the oak floor of the German Clock Museum in Furtwangen. Such classic examples are both admired by and subject to heavy usage from the public. However, the greatest number of floors, either sealed or oiled with eukula products are found in private homes, where only guests can admire them. We take great satisfaction in knowing that floors protected with eukula are praised and admired worldwide. The results are long lasting beauty and carefree protection of fine natural wood.

eukula:
The Best in Wood Floor Protection.



eukula GmbH

Am Bahnhof 6, Döggingen

78199 Bräunlingen

GERMANY

Phone +49 77 07 / 151-248

Fax +49 77 07 / 151-245

eMail: vertrieb@eukula.de

Internet: www.eukula.de