



## Oil or Hardwax Oil

**We offer both.**

**Only your know-how can even improve it**

<b>euku-öl 1 HS</b>	based on vegetable products, solid content of 90% for matt surfaces
+ <b>euku-pflegeöl</b>	for maintaining the matt surface of euku-öl 1 HS
<b>euku-öl 2 Plus HS</b>	Hardwax oil, oiling and waxing in one procedure, for an even and satin surface, solid content of 80%
+ <b>euku-refresher</b>	for the maintenance of oiled floors

**The convincing combination for finishing the oiled surface in one day.**

### **The result:**

A natural surface, less sensible to dirt and humidity, fast drying.

Sand the floor with 120 grid, apply the **euku-öl 1 HS** or **euku-öl 2 Plus HS** and treat it immediately with the beige or red pad. Do not let it dry. Afterwards apply the **euku-pflegeöl resp. euku-refresher** with a trowel or big surfaces with the T-Wischer (T-frame) and use the beige or red pad. Then put the the euku-poliertuch (polishing cloth) around the pad and polish the surface with a single disc machine.

The floor is getting a bit smoother, the surface is more closed and therefore less sensible to humidity and dirt, a natural looking surface which accentuates the natural grain of wood.

Your customer will enjoy it!

### **Tools:**

Beige or red pad

Trowel

euku-polierwolltuch (polishing cloth)

Use Strato 101 and

the darkening of the gaps

under oil is history.