

Technical Data Sheet**euku-conditioner for cleaning wood**

- ◆ biodegradable
- ◆ easy application
- ◆ for cleaning the surface

Substrate:

Wood deckings, terraces, garden furniture etc.

Application:

Apply the euku-conditioner undiluted, leave the surface for 15 – 30 Min. Scrub the soaked wood with a stiff brush and a lot of water.

Wash down the wood thoroughly with clear water.

Repeat the cleaning if necessary.

Drying:

Apply euku-exterior oil after the wood has dried completely.

Storage:

The material can be stored in cool and dry condition in their original containers up to approx. 24 months (storage and transportation +5 °C to +40 °C).

Consumption:

50 - 80 ml/sqm. depending on the kind of surface.

Hazardous Goods Marking:

GefStoffV:	Xn Harmful
VbF:	not applicable
ADR-RID:	not applicable
UN-Nr.:	not applicable
R-Terms:	21/22 Harmful in contact with skin and if swallowed
S Terms:	36/37 Wear suitable protective clothing and gloves
	38 In case of insufficient ventilation, wear suitable respiratory equipment.
	23 Do not breathe vapour.

Contents: Details in Accordance with EC Recommendations:

Oxalic acid, biodegradable
Solvent: water

Further information see our material safety data sheet.

eukula-

Gesellschaft moderner Kunststoff- und Lackbeschichtungen mbH

Döggingen Am Bahnhof 6 D-78199 Bräunlingen Tel. +49(0)7707.151-206 und 151-248 Fax +49(0)7707.151-245 E-Mail: vertrieb@eukula.de Internet: <http://www.eukula.de>

Unsere Technischen Datenblätter sollen nach dem aktuellen Kenntnisstand beraten. Diese Hinweise befreien Sie jedoch nicht von einer eigenen Prüfung unserer Produkte in Hinblick auf ihre Eignung für die beabsichtigten Verfahren und Anwendungen. Der Verkauf unserer Produkte erfolgt nach Maßgabe unserer Geschäfts- und Lieferbedingungen.

Stand: 10 2010 Mit dieser Auflage sind alle früheren Merkblätter für dieses Produkt ungültig.