

Technical Data Sheet**euku-öl color
Color Concentrate****for tinting euku-öl 1/euku-öl 1 HS or euku-öl 2 Plus/euku-öl 2 Plus HS**

- ◆ gives a tinted accent to oiled surfaces
- ◆ maintains the grain of the wood
- ◆ variable in color

Available Colors:

- ◆ teak
- ◆ antique
- ◆ black
- ◆ silver metallic
- ◆ white
- ◆ oak
- ◆ green
- ◆ yellow
- ◆ red
- ◆ blue
- ◆ ochre yellow
- ◆ brown
- ◆ basalt grey

mixable among each other.

Admixture:

Up to 30% to euku-öl 1, euku-öl 1 HS or euku-öl 2 Plus, euku-öl 2 Plus HS.

We recommend first making a trial area on a section of the wood floor to ascertain the color desired.

Application:

Shake or stir euku-öl color well before use. Depending on the color intensity, add 30% of euku-öl color, to euku-öl 1/euku-öl 1 HS or euku-öl 2 Plus/euku-öl 2 Plus HS and shake well. Apply the tinted material evenly and continuously without any interruption. See also the application notes for the euku-oils 1, 1HS, 2 Plus and 2 Plus HS. When oiling in one day the euku-öl color has to be added to the euku-pflegeöl resp. the euku-refresher accordingly.

Drying and Consumption:

See the application notes for euku-öl 1, euku-öl 1 HS and euku-öl 2 Plus, euku-öl 2 Plus HS.

Cleaning of Tools:

Immediately after use with UA Dilution V 28 or Washing Dilution V 29.

Storage:

Store in cool and dry condition in their original container, up to 12 months.

Hazardous Goods Marking:

GefStoffV:	Not applicable
VbF:	Class A II
ADR-RID:	Class 3
UN-Nr.:	1263
Giscode:	Ö 60
R Terms:	10 Flammable 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 66 Repeated exposure may cause skin dryness or cracking. S Terms: 24 Avoid contact with skin. 38 In case of insufficient ventilation, wear suitable respiratory equipment. 51 Use only in well-ventilated areas. 61 Avoid release to the environment. Refer to special instructions/safety data sheets. 23 Do not breathe vapour. P Terms 99 Contains 2-butanone oxime. May produce an allergic reaction.

Do not leave any flowers, aquariums or food in the room.

Disposal:

The material should not be allowed to enter water courses. Not set material should be treated as special waste.

Warning – Self Ignition

Application cloth, rags, fleece, sanding dust etc. saturated with the oil or refresher, must be sealed off air tight in a metal box or soaked in water and be disposed of without risk of fire.

Maintenance:

See the application notes for euku-öl 1 / euku-öl 1 HS resp. euku-öl 2 Plus / euku-öl 2 Plus HS. Re-coat worn out areas if necessary with tinted oil.

Further information see our material safety data sheet.

eukula

Gesellschaft moderner Kunststoff- und Lackbeschichtungen mbH

Döggingen Am Bahnhof 6 D-78199 Bräunlingen Tel. +49(0)7707.151-206 und 151-248 Fax +49(0)7707.151-245 E-Mail: vertrieb@eukula.de Internet: <http://www.eukula.de>

Unsere Technischen Datenblätter sollen nach dem aktuellen Kenntnisstand beraten. Diese Hinweise befreien Sie jedoch nicht von einer eigenen Prüfung unserer Produkte in Hinblick auf ihre Eignung für die beabsichtigten Verfahren und Anwendungen. Der Verkauf unserer Produkte erfolgt nach Maßgabe unserer Geschäfts- und Lieferbedingungen.

Stand: 10 2010 GB Mit dieser Auflage sind alle früheren Merkblätter für dieses Produkt ungültig.

How to oil your floor correctly

- Please observe carefully our Technical Data Sheets.
- Regular and even sanding is the main condition to achieve a uniform surface particularly in case of colour oils. Different ways of sanding, e.g. sanding to the edge, may create light and dark margins which are even more visible in case of colour oils.
- Sanding traces because of e.g. small stones in the sanding belt appear after the oiling as stripes.
- When oiling tropical wood there might be a delay in drying due to its ingredients.
- In case of highly absorbing woods like maple, beech, cherry etc. a sufficient material quantity should be applied to achieve an even saturation of the wood. In case of lack of material the surface tends to be more susceptible to dirt and stains and to greying.
- The use of a three disc machine is recommended.
- ATTENTION: Too fine sanded wood may disturb the oil penetrating into the wood.

Please note:

- Please follow our maintenance instructions for oiled floors.
- Unsuitable cleaning and maintenance products may harm the surface.
- Oiled surfaces are open-pore and thus more sensitive regarding humidity. Remove water immediately from the oiled surface.
- Maintain oiled floors according to their use.
- For the oil/water based combination ensure good ventilation (fresh air supply) when drying.

eukula

Gesellschaft moderner Kunststoff- und Lackbeschichtungen mbH

Döggingen Am Bahnhof 6 D-78199 Bräunlingen Tel. +49(0)7707.151-206 und 151-248 Fax +49(0)7707.151-245 E-Mail: vertrieb@eukula.de Internet: <http://www.eukula.de>

Unsere Technischen Datenblätter sollen nach dem aktuellen Kenntnisstand beraten. Diese Hinweise befreien Sie jedoch nicht von einer eigenen Prüfung unserer Produkte in Hinblick auf ihre Eignung für die beabsichtigten Verfahren und Anwendungen. Der Verkauf unserer Produkte erfolgt nach Maßgabe unserer Geschäfts- und Lieferbedingungen.

Stand: 10 2010 GB Mit dieser Auflage sind alle früheren Merkblätter für dieses Produkt ungültig.