

Technical Data Sheet**euku-polish plus**

Floor Care, solvent based

- ◆ for sealed and impregnated floors
- ◆ for solvent resistant floors
- ◆ waterproof, easy to polish

Substrate:

Solvent based sealed and impregnated wood floors. Not for water based sealed wood floors.

Application:

Spread euku-polish plus thin on the cleaned floor by using a cloth or mop and polish the floor as soon as it is dry. A multi-purpose machine with a pad is strongly recommended. euku-polish plus treated floors are water-resistant and can be polished again after cleaning with a damp cloth.

Application	Tool	Drying Time
<u>Coating:</u> 1 x euku-polish plus	Cloth/Pad	approx. 30 min.

Drying:

The drying times are approximate, depending on the room and floor temperature as well as the air humidity.

Consumption:

approx. 10 - 20 ml/sqm.,
1 ltr. – approx. 50 – 100 sqm.

Cleaning of Tools:

Immediately after use with water. Can be removed with Diluting Agent for Cleaning V 29.

Storage:

Store in cool and dry condition in their original container, up to 12 months.

Hazardous Goods Marking:

GefstoffV: Not applicable
VbF: A II
ADR-RID: Class 3
UN-Nr.: 1263
R Terms: 10 Flammable
S Terms: 1/2 Keep locked up and out of reach of children.
23 Do not breathe gas/fumes/vapour/spray.
24 Avoid contact with skin.
29/56 Do not empty into drains, dispose of this material and its container to hazardous or special waste collection point.
43 In case of fire, use (indic. the precise type of fire-fighting equip. If water increases the risk, add – Never use water)
46 If swallowed, seek medical advice immediately and show this container or label

UBA-Nr.: 19590006

Disposal:

The material should not be allowed to enter water courses. Not set material should be treated as special waste.

Further information see our material safety data sheet