

**Technical Data Sheet****euku-reiniger**

- ♦ strong cleaner for waxy, greasy and dirty floor surfaces
- ♦ removes stains and shoemarks
- ♦ deep cleaner for floors treated with euku-pflegeöl and euku-refresher

**Substrate:**

All solvent resistant and wax treated floors.

**Application:**

Basic Cleaning:

Spread out euku-reiniger on the floor. Leave it on for some minutes and scrub the floor with a cleaning machine or pad. The solvent wax film has to be taken off with a cloth as long as the surface is still wet. Please clean the cloth in between with lukewarm water and repeat it again. After the floor is completely dry, apply euku-polish, euku-refresher or euku-pflegeöl and polish it.

Intermediate Cleaning:

Clean the floor with a euku-reiniger damped cloth and polish it afterwards with a white pad. Stains and shoemarks disappear.

**Consumption:**

Basic Cleaning: 2-4 l per 100 sqm.  
depending on the condition of the floor.  
Regular cleaning 200-400 ml per 100 sqm.

**Storage:**

Store in cool and dry condition in their original container, up to 18 months.

**Contents:**

> 30 % aliphatic hydrocarbon.  
Further contents: scents.

**Disposal:**

The material should not be allowed to enter water courses. Not set material should be treated as special waste.

**Hazardous Goods Marking:**

GefStoffV: Xi Irritant  
N Dangerous for the environment  
contains: Orangerterpene  
VbF: All  
ADR-RID: 3  
UN-Nr.: 1993  
R Terms: 10 Flammable  
38 Irritating to skin  
43 May cause sensitisation by skin contact.  
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
S Terms: 24 Avoid contact with skin.  
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
37 Wear suitable gloves.  
51 Use only in well-ventilated areas.  
61 Avoid release to the environment. Refer to special instructions/safety data sheets.

UBA-No.: 19590005

**Warning – Danger of Self-Ignition:**

Application cloth, rags, fleece, sanding dust etc. saturated with oil or refresher etc., must be sealed of air tight in a metal box or soaked in water and be disposed of without risk of fire.

Further information see our material safety data sheet.

eukula-

Gesellschaft moderner Kunststoff- und Lackbeschichtungen mbH

Döggingen Am Bahnhof 6 D-78199 Bräunlingen Tel. +49(0)7707.151-206 und 151-248 Fax +49(0)7707.151-245 E-Mail: [vertrieb@eukula.de](mailto:vertrieb@eukula.de) Internet: <http://www.eukula.de>

Unsere Technischen Datenblätter sollen nach dem aktuellen Kenntnisstand beraten. Diese Hinweise befreien Sie jedoch nicht von einer eigenen Prüfung unserer Produkte in Hinblick auf ihre Eignung für die beabsichtigten Verfahren und Anwendungen. Der Verkauf unserer Produkte erfolgt nach Maßgabe unserer Geschäfts- und Lieferbedingungen.

Stand: 05 2010 1 GB Mit dieser Auflage sind alle früheren Merkblätter für dieses Produkt ungültig.