

**Technical Data Sheet****euku-wachsentferner mit Aktivlöser**

euku-wax remover with active solvent

- ◆ may be mixed with water
- ◆ special low-foam solvent for removing shiny or bees wax coatings on heavily soiled floors
- ◆ heavily diluted, also suitable for use as a general cleaner

**Substrate:**

Suitable for all sealed floors treated with a wax containing product.

**Application:**

Basic cleaning:

Depending on the stubbornness of dirt and the wax layers add between 1 – 2,5 litres of euku-wax remover and wipe over the surface with a damp cloth. Whilst the loosened dirt is still wet, absorb it using a cloth. Finally wipe using clean water.

Intermediate cleaning:

When only the dirt is to be removed, wipe over the surface use 100 to 200 ml of euku-wax remover diluted with 10 litres of water.

Maintenance:

Once the cleaned floor is dry, apply euku-polish or euku-wax antislip, depending on the type of floor.

**Consumption:**

Basic Cleaning: 1-2,5 l euku-wachsentferner to 10 ltr. water for approx. 100 sqm.

Regular cleaning: 100-200 ml to 10 l water for approx. 100 sqm.

**Storage:**

Store in cool and dry condition in their original container, up to 12 months.

**Hazardous Goods Marking:**

GefStoffV: Xn irritant

VbF: not applicable

ADR-RID: not applicable

UN-Nr.: not applicable

R Terms: 36 Irritating to eyes

S Terms: 1/2 Keep locked up and out of reach of children.

25 Avoid contact with eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

46 If swallowed, seek medical advice immediately and show this container or label.

UBA-No.: 19590002

**Disposal:**

The material should not be allowed to enter water courses. Not set material should be treated as special waste.

**Contents:**

Less than 5% nonionic surfactants, less than 5% NTA. Further ingredients: perfume oil, LIMONENE. The product is harmless to the environment in accordance with the regulations set for washing and cleaning materials.

pH value: approx. 7

Further information see our material safety data sheet

eukula-

Gesellschaft moderner Kunststoff- und Lackbeschichtungen mbH

Döggingen Am Bahnhof 6 D-78199 Bräunlingen Tel. +49(0)7707.151-206 und 151-248 Fax +49(0)7707.151-245 E-Mail: [vertrieb@eukula.de](mailto:vertrieb@eukula.de) Internet: <http://www.eukula.de>

Unsere Technischen Datenblätter sollen nach dem aktuellen Kenntnisstand beraten. Diese Hinweise befreien Sie jedoch nicht von einer eigenen Prüfung unserer Produkte in Hinblick auf ihre Eignung für die beabsichtigten Verfahren und Anwendungen. Der Verkauf unserer Produkte erfolgt nach Maßgabe unserer Geschäfts- und Lieferbedingungen.

Drucknummer: 326 Stand: 03 2008 1 GB Mit dieser Auflage sind alle früheren Merkblätter für dieses Produkt ungültig.