

Technical Data Sheet

**Strato Quick Start
Strato Quick Finish satin**

1C Wood Floor Sealing System
water based, quick drying

- ◆ 1 Day System
- ◆ no intermediate sanding necessary
- ◆ easy to apply

Substrate:

Soft and hard wood floors in a dry, oil, wax and dust free condition. Should not be used for underfloor heating.

Application:

Shake well before application. Use a trowel resp. a roller. The room and floor temperature should be min. +15 °C. Draughts and direct sunlight should be avoided.

Strato Quick Start

Water based trowel primer with a high solid content for the one day system.

Strato Quick Finish

Water based 1C Sealer. High viscosity for high coat thickness.

Application

Tool

Drying Time

Priming:

1x Strato Quick Start



20 min.

1x Strato Quick Start



20 min.

1x Strato Quick Start



1 h

Coating:

1 x Strato Quick Finish



ca. 12h

Final hardness:

after approx. 5 days

Drying:

The drying times are approximate, depending on the room and floor temperature as well as the air humidity.



Consumption:

Strato Quick Start ca. 30 ml/m² per coat
Strato Quick Finish ca. 190 ml/m² per coat.

Cleaning of Tools:

Immediately after use with water. Dried on material can be removed with Diluting Agent V 29.

Storage:

Store in cool and dry condition in their original container for up to 6 months. Protect from frost.

Dangerous Goods Marking: Strato Quick Start

GefStoffV: not applicable
VbF: not applicable
ADR-RID: not applicable
UN-Nr. not applicable
Giscode: W 2+
R-Sätze: none
S-Sätze: 38 In case of insufficient ventilation, wear suitable respiratory equipment
23 Do not breathe vapour

Dangerous Goods Marking: Strato Quick Finish

GefStoffV: not applicable
VbF: not applicable
ADR-RID: not applicable
UN-Nr. not applicable
Giscode: W 3+
R-Sätze: none
S-Sätze: 38 In case of insufficient ventilation, wear suitable respiratory equipment
23 Do not breathe vapour

Disposal:

Do not dispose of in water courses. Dried material should be disposed of in appropriate facility.

Maintenance:

For cleaning, put euku-clean in the wiping water and for maintenance use euku-wax anti-slip.

For further information see our material safety data sheet.

eukula-

Gesellschaft moderner Kunststoff- und Lackbeschichtungen mbH

Döggingen Am Bahnhof 6 D-78199 Bräunlingen Tel. +49(0)7707.151-206 und 151-248 Fax +49(0)7707.151-245 E-Mail: vertrieb@eukula.de Internet: <http://www.eukula.de>

Unsere Technischen Datenblätter sollen nach dem aktuellen Kenntnisstand beraten. Diese Hinweise befreien Sie jedoch nicht von einer eigenen Prüfung unserer Produkte in Hinblick auf ihre Eignung für die beabsichtigten Verfahren und Anwendungen. Der Verkauf unserer Produkte erfolgt nach Maßgabe unserer Geschäfts- und Lieferbedingungen.

Drucknummer: 332 Stand: 05 2009 Mit dieser Auflage sind alle früheren Merkblätter für dieses Produkt ungültig.